

The

**BRIGHT**

**IDEAS**

Co (UK) Ltd

Hainge Road, Tividale, West Midlands, B69 2ND, England (UK)

## LTP Grout & Tile Protector Data Sheet

Welcome to the Bright Ideas Data Sheet for the LTP Grout and Tile Protector. This data sheet will help you by providing helpful tips and instructions on how to use the LTP Grout and Tile Protector in different areas and also provide you with a number of health and safety tips to be aware of.

### ● LTP Grout and Tile Protector...

The LTP Grout and Tile Protector forms a colourless barrier which helps to protect porous wall and floor grout joints from penetration by water, dirt, grease, oil and limescale, making treated surfaces much easier to keep clean. It is highly recommended for use in wet rooms and shower enclosures. Primarily used as a 'top up coat,' this product further enhances the protection of natural stone and other types of masonry surfaces. Overspray on most surfaces will dissipate completely, leaving little or no residue to remove. When sealing a porous stone it is advisable to use a suitable liquid impregnator before proceeding with the LTP Grout and Tile Protector to achieve the best result.

### ● Coverage Per 600ml...

600 linear metres depending upon the size of the grout joint and number of coats required. 5 to 25sq.m of tile and grout depending upon the porosity and the number of coats required.

### ● Directions of Use...

Areas to be treated must always be cleaned. This includes any older or contaminated grouting which must be rinsed thoroughly. Any newly grouted surfaces must be left to cure for 20-30 minutes and must be free of dust before application. It is recommended to always test the product on an inconspicuous area for suitability before general application. Always shake the can well before use. Spray the can 15 to 20cm away from the surface, spraying a sweeping motion. Touch dry within 5 minutes. A 2-3 hour curing time should be allowed upon completion before use. Test the area after application with a little water to see if the water is absorbed. A second and third coat may be required to achieve maximum performance. Use only in open or well ventilated areas. Open windows and if possible use fans to circulate air. A suited dust mask is also recommended to prevent breathing in toxins. Any overspray on highly polished porcelain or stone and highly glazed surfaces may sometimes leave a slight residue. Use a small wipe to wipe up any excess within 5 minutes. Stubborn residues left on the surface can be removed with the application of more LTP Grout and Tile Protector which should be buffed off immediately. Do not spray on acrylic or stained surfaces such as cabinets and stained timber skirting boards. Mask and protect these surfaces before application.

### ● Maintenance...

Do not use harsh abrasive cleaning agents. Clean treated areas with water and a mild PH neutral detergent. In some instances it may be necessary to use a stronger cleaner to remove stubborn surface marks, in which case you may need to re-seal treated areas.

### ● Health and Safety...

Extremely flammable and irritating to skin. Very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. Vapours may cause drowsiness or dizziness. Keep out of reach of children. Keep away from sources of ignition. No smoking. Do not breathe in vapours / spray. Avoid contact with eyes and skin. Do not empty into drains. Use only in well-ventilated areas. Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50 C. Do not pierce or burn even after use. Do not spray onto a naked flame or any incandescent material.



Contact Information:  
Tel: 0121 520 9200  
Email: sales@thebrightideas.co.uk